



Harald Pettersen - Statoll ASA



Technical specifications

- Part no: 85037
- Operating temp: -20/+55
- Housing: Polyamide PA6
- IP grade: IP67 water proof
- Weight: 0,2 kg
- Size: 72 x 50 x 29 mm.
- Mounting Clip: Stainless steel
- Spiral cable: Length, 40-120 cm max
- Connector headset: Nexus TP120 (Peltor pinning)

Jatronic PTT switch for SEPURA STP8X TETRA ATEX



Jatronic launches the new AB12-36T customized for SEPURA STP8X

Excellent sound reproduction, full duplex functionality and all the well-known characteristics of the AB12 have of course been kept. AB12-36T has a good grip and is responsive even when using thick gloves. The AB12-36T is approved in accordance with EN 60079-0:2012, EN 60079-11:2012 and IEC 60079-0:2011, IEC 60079-11:2011

AB12-36T can be connected to Ex approved headsets with dynamic microphone and Nexus TP120 plug with 4 pole connectors. Refer to ATEX certificate no. Nemko 03 ATEX 165X or IEC Ex NEM 13.0012X for electrical parameters.



Example in use.

Dealer:



Borgeskogen 5, 3160 Stokke | Phone: +47 33 08 36 60 | post@jatronic.no